

PICOTE PROLITE MILLERS

High-Speed Drain Cleaning. Lightweight Power. Professional Results.



Built for drain cleaning, descaling, and blockage removal in small to mid-sized pipes, the Picote ProLITE Millers deliver professional-level performance in a compact, lightweight form.

Powered by an 18V Li-ion battery, these versatile units provide exceptional portability & freedom on-site without sacrificing cleaning power.

Designed with operator safety, efficiency, and durability in mind, they are ideal for residential, commercial, & maintenance plumbing professionals.

With multiple tooling options, variable speed control, & cordless convenience, the ProLITE Series gives you the power & flexibility to tackle tough jobs anywhere.

USES AND BENEFITS

- **Lightweight Design.** ProLITE 6 is only 13.6kg (30 lbs) & ProLITE 8 is 14.6kg (32 lbs).
- **Compact & Portable:** Ergonomic handle and compact size for easy transport and storage.
- **Cordless Freedom:** Includes single slot battery charger and a Picote Li-ion 18V / 5.0Ah battery in a carrying tool bag. Add a dual slot charger with 2 extra batteries for even more run time & convenience.
- **Variable Speed Control:** Infinitely adjustable from 850-2150 RPM for precision cleaning in varied conditions.
- **Electronic Safety Clutch:** Eliminates kickback risk and improves operator & equipment protection.
- **Power:** Up to 20 minutes runtime at full load.
- **Fast Recharge:** 1 Hr 40 min from empty to full.
- **Tool Compatibility:** Compatible with a wide range of Picote tools including Original Chains (PVC, Standard, & Tiger), Drill Heads, Picote Smart Cutter™, Nylon Cleaning Brushes, & additionally for ProLITE 8: Smart Sweeper, 3D Chains (PVC & Premium), Cyclone Chains (PVC, Standard, Tiger, & Premium), Tiger Drill Chains & Wire Cleaning Brushes.

Technical Specifications

Category	Measurement
ProLITE 8	
Cleaning / Descaling	DN50-100 (2-4")
Usable Shaft Length	14m (45.9')
Weight	14.6kg (32 lbs)
Shaft Size	8mm (½")
ProLITE 6	
Cleaning / Descaling	DN32-75 (1¼-3")
Usable Shaft Length	19m (62.3')
Weight	13.6kg (30 lbs)
Shaft Size	6mm (¼")
Universal ProLITE Specifications	
Size (HxWxL)	62x27x52cm (24.4x10.6x20.5")
Speed (variable)	850-2150 RPM
Power	Li-ion 18V / 5.0Ah Battery
Run Time	20 Minutes (at full load)
Battery Recharge Time	1hr 40min (empty to full)
Safety Features	Protective outer shaft casing, operator presence foot control, electronic safety clutch



More Info/Guides/Technical Support:

- Visit picoteinstitute.com for e-learning courses, educational videos, quick guides, & manuals.
- For more information on products, spare parts, assembly and operation, consult the Super Midi Miller Manual or contact Picote Technical Support.
- For hands-on product training, Picote operates training centers in USA, UK, and Finland.

PRODUCTS AND SPARE PARTS

Picote Pro LITE Millers Products and Parts	
Part Number	Description
3510000620US	Picote ProLITE 6 Miller, US
3510000815US	Picote ProLITE 8 Miller, US
Parts & Accessories	
3510000001	Picote Li-ion 18V 5.0Ah Battery
3510000003US	Dual Slot Charger with 2x Picote Li-ion 18V, 5.0Ah Batteries, US
1350000020	Picote Flexible Shaft Lubricant Bottle (0.5 litres/17oz)
1350000021	Picote Flexible Shaft Lubricant Package (6 bottles)

